TECHNICAL **SPECIFICATION**



EVOLite® Skyworker[™] Micro Peak Revolution®Wheel Ratchet Vented

White / AJS260-000-100



DESCRIPTION

The EVOLite® Skyworker™ helmet has a suspension system and shell structure that has been designed to be used for industrial, mountaineering, rescue and leisure activities.

Helmets conforming to the EN 12492 mountaineering standard are impact tested with two 5kg strikers. A hemispherical striker is dropped from 2 metres onto the crown of the helmet and a flat striker from 500mm on to the front, rear or side by tilting the headform to 30°. In all cases, the transmitted force through the neck of the headform must not exceed 10kN. Two penetration tests with a 3kg pointed striker are also performed within a 50mm radius of the helmet's crown without making contact with the headform.

Meets the mandatory shock absorption and penetration resistance requirements of EN 397 industrial helmet standard.

OPTIONS

Black (AJS260-001-100) Blue (AJS260-000-500) Green (AJS260-000-300) Grey (AJS260-000-400) Orange (AJS260-000-800) White (AJS260-000-100) Yellow (AJS260-000-200)

SAFETY STANDARDS

EN 12492 • EN 397



Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have



Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

inaccuracies and should not be relied upon.

SPECIFICATIONS				
	Peak Micro		Impact Resistance 100 Joules	
-	Side Impact Resistance 25 Joules	*	Maximum Temperature +50°C	
	Minimum Temperature -40°C	ABS	ABS Shell Yes	
E	Recyclable Shell	- <u> -</u> - - -	Textile Harness	
30)	Depth Adjustment 3D Harness		Wheel Ratchet Yes	
	Universal Accessories Slot Yes		Ventilation Yes	
60	Reflective Option Optional		ID card holder Optional	
(bsi)	BSI Kitemark Yes		Fitted 4 point chinstrap (EN12492 Compliant) Fitted	
¥	JSPCheck Yes		Product Weight 382g	
÷	Size 53-64cm			

FEATURES



EPS Liner

Side, front and rear impact protection from the shock absorbing EPS liner. The liner is vented to increase comfort whilst maintaining a high protection factor.



CR2[™] Reflective

Using Class RA2, high intensity reflective. CR2[™] is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Most Secure Fit

Fully adjustable 4-point chinstrap with quick release buckle. Easy to use Revolution® wheel ratchet and 3D Adjustment that offers 1-2-3 point harness depth settings for a perfect fit.



Ventilation

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



Supreme Comfort

6-point textile cradle harness system with 3D Adjustment offering 1-2-3 point harness depth settings and a Chamlon[™] cotton sweatband.



Accessories

Universal attachment slots enable firm fitting of a range of safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



LOGO	RANGE
 ✓ Front ✓ Back ✓ Sides 	SKYWORKER
VIDEOS	DOWNLOADS
www.youtube.com/watch?v=2X3TSz5STxw	Image Pack (ZIP) doc-evolite-skyworker.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.