

TRYON OTG

ULTRA-COVERING

TRYON is available in Premium OTG version. Beneficiating from PLATINUM® coating, maximal covering, extendable temples allowing a precise adjustment to every wearer. TRYON OTG is compatible with most of prescription spectacles.



41g



TRYOTGPSI











TRYOTGPSF

- + SOFT UPPER PROTECTION (TPR)**
- + PLATINUM® COATING ( P)**
- + CO-INJECTED PC/TPR ADJUSTABLE AND EXTENDABLE TEMPLES**
- + FLEX 160° TEMPLES**

bollé
SAFETY

TRYON OTG

ULTRA-COVERING

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-----------|-----------------------------------------------------------------------------------------|------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| TRYON OTG |  Clear | TRYOTGPSI | 2C-1,2  1 FT KN €€ |  EN166 FT €€ | Anti-scratch/Anti-fog  |
| |  Smoke | TRYOTGPSF | 5-3,1  1 FT KN €€ |  EN166 FT €€ | Anti-scratch/Anti-fog  |

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:


F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging


€€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGIES



The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| PACKAGING AND EAN13 CODE | | |
|-------------------------------|---------------|---------------|
| | TRYOTGPSI | TRYOTGPSF |
| Individual plastic bag | 3660740008307 | 3660740008420 |
| 10 spectacles per inner box | 3660740108304 | 3660740108427 |
| 180 spectacles per outer pack | 3660740208301 | 3660740208424 |

| CHARACTERISTICS | |
|------------------|-----------------------|
| LENSES | PC - 2,2 mm - Curve 4 |
| FRAME | - |
| TEMPLES | PC + TPR |
| UPPER PROTECTION | TPR |
| SPARE LENSES | No |



Non-contractual pictures

18/04/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY