

# Technical Data Sheet

## Particle filtering half mask

### Dräger X-plore 1320 FFP2 NR D

1.0	General Data	
1.1	Manufacturer	ACE Protection AB, Svenljunga, Sweden, a Dräger Safety company for Dräger Safety AG & Co. KGaA, Revalstraße 1, D - 23560 Lübeck, Germany
1.2	Designation	Dräger X-plore 1320 FFP2 NR D
1.3	Dräger part no.	39 51 213
1.4	Intended use	Protection against solid and liquid particles. Scope of protection as indicated by product documentation, technical standards and installed application rules.
1.5	Relevant standards	EN 149: 2001 + A1: 2009 (Particle filtering half masks)
1.6	Approval	CE type approval test certificate, tests carried out and granted by accredited and notified body Institut für Arbeitsschutz der Deutschen gesetzlichen Unfallversicherung (BGIA).

2.0	Design & Construction	
2.1	Materials	<p>Particle filter: Mechanical and electrically charged non-woven material.</p> <p>Head strap: Natural rubber latex covered with woven textile. The natural rubber latex will not make contact with the skin.</p> <p>Nose clip: Plastic (LLDPE) coated metal wire, free of aluminium</p>
2.2	Construction	The filtering face piece X-plore 1320 FFP2 NR D consists of several layers of non-woven materials, partly with electrical charge.
2.3	Working principle	Particle filtration by combined electro charged and mechanical filter media.
2.4	Shelf life	4 years
2.5	Dimensions	125 x 140 x 54 mm
2.6	Weight	Excl. package: 14,0 g

# Technical Data Sheet

## Particle filtering half mask

### Dräger X-plore 1320 FFP2 NR D

3.0	Performance Data	(minimum data in accordance with standard, incl. loading test with 120 mg paraffin oil)		
3.1	Particle filtration efficiency	Test aerosols: Minimum efficiency (EN 149):	sodium chloride: 94 % paraffin oil: 94 %	
3.2	Gas filtration capacity Laboratory test results	Not applicable		
3.3	Breathing resistance inhalation	at 30 litres/min, constant flow	Max. 0,7 mbar	(EN 149)
		at 95 litres/min, constant flow	Max. 2,4 mbar	(EN 149)
	Breathing resistance exhalation	at 160 litres/min, constant flow	Max. 3,0 mbar	(EN 149)
3.4	Dolomite clogging test	Passed		

4.0	Documentation			
4.1	Markings	Label: markings in accordance with EN 149:2001 + A1: 2009, expiry date, producer and approval number. Approval marking: CE 0158.		
4.2	Instructions for use	Each smallest packing unit of masks is accompanied by an instruction for use.		

5.0	Packing & Packaging			
5.1	Packing	The masks are packed hygienically in a plastic bag inside the box.		
5.2	Packaging units	20 pcs. each box		

6.0	User notes and limitations	The particle filtering half mask conforms to the minimum requirements of the standard indicated by the class and type of the filter it is marked with. It must be noted that laboratory values can differ from those measured in practice. This may result in longer or shorter break through times. The user must read and understand the instructions for use. Additionally the knowledge of all relevant application rules is mandatory (see in particular the limitations in use). Further information on request.		
-----	----------------------------	--	--	--

Dräger Safety AG & Co. KGaA