


ELIPSE® HALF-FACE MASK + HESPA[™] P3 DUST (R) Filters







Encapsulation (patented technology) 645 mm; lenght of actual media in each filter

Applications - dust, mist and fumes

Welding and Grinding



Metal Fumes and Dust



Manufacturing Glass Fibres, Composite Fibres, Lead Fumes



Construction Silica Dust, Abestos, Concrete Dust, Stone Dust, Aggregate Dust, Wood Dust, Cement Dust, Mold

Food Poultry, Powders (Dairy), Spices, Grain Dust

Efficiency P3 >99,95% for 0,3 µ particulate

CE 2797 Weight

Standards

EN140: 1998 Mask Body

EN143: 2000+A1: 2006 P3 RD

Mask + Filter: net (S/M) 130 g; (M/L) 138 g gross (S/M) 185 g; (M/L) 193 g Filter: net 18 g each; both net 36 g, gross 59 g

Shelf Live

5 years (mask & filters) See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Material

- Mask: Medical grade TPE Conforms to ISO 10993-10: 2010 for irritations. Mask body latex and silicone free, odour free.
- Valve Body in Nylon, Inhalation/Exhalation diaphragm in Silicone.
- 4 point adjustable elasticated head and neck strap with comfort pad in TPE. Filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated.

Production

United Kingdom 100% of filters NaCl Tested

Code Description Quantity **Elipse Half Mask** 10 pcs. per PR299 (S/M SPR501 (M/L) complete with P3 filters box SPR316 **Elipse P3 replacement filters** 10 sets of 2 pcs. per box SPM001 **Elipse Dust Mask Carry Case** 10 sets per (Belt holder) box SPM414 Portacount Face Fit Kit adaptor <u>10 sets</u> per box

Mining



Pharmaceutical



ISSUE date 18/02/21 ISSUE n. 3

GVS Filter Technology UK NFC House - Vickers Industrial Estate - Mellishaw Lane, Morecambe Lancashire LA3 3EN - tel. +44 (0) 1524 847600 - gvsuk@gvs.com www.gvs.com