# SLAM

## ULTRA

Stylish and easy-to-wear. The SLAM model provides protection at all times while offering unbeatable comfort.

SLAPSI

SLAPSF

SLAPSJ

SLAESP

SLAWPCC2

SLAWPCC3

SLAWPCC5

**24 g**

**SUPPLIED WITH**

**Adjustable cord**
**CORDC**

- **WRAP-AROUND FIT**
- **ALL-ROUND VISION**
- **COMFORTABLE STRAIGHT TEMPLES**

bollé SAFETY

# SLAM

## ULTRA-TRENDY

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|---|---|---|---|---|---|
| SLAM | Clear | SLAPSI | 2C-1,2 1 FT CE | EN166 FT CE | Anti-scratch/anti-fog |
| | Smoke | SLAPSF | 5-3,1 1 FT CE | EN166 FT CE | Anti-scratch/anti-fog |
| | Yellow | SLAPSJ | 2C-1,2 1 FT CE | EN166 FT CE | Anti-scratch/anti-fog |
| | ESP | SLAESP | 5-1,4 1 FT CE | EN166 FT CE | Anti-scratch |
| | Welding shade 1,7 | SLAWPCC2 | 1,7 1 FT CE | EN166 FT CE | Anti-scratch |
| | Welding shade 3 | SLAWPCC3 | 3 1 FT CE | EN166 FT CE | Anti-scratch |
| | Welding shade 5 | SLAWPCC5 | 5 1 FT CE | EN166 FT CE | Anti-scratch |

### LENS MARKING

**Optical class symbols:**

**1.** Continuous work

**Mechanical strength symbols:**

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**Others symbols:**

CE European standard Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

CE European standard Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### TECHNOLOGY

**ESP**

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

**PACKAGING AND EAN13 CODE**

| | SLAPSI | SLAPSF | SLAPSJ | SLAESP | SLAWPCC2 | SLAWPCC3 | SLAWPCC5 |
|---|---|---|---|---|---|---|---|
| Individual plastic bag | 3660740001087 | 3660740001094 | 3660740001100 | 3660740001117 | 3660740001124 | 3660740001131 | 3660740001148 |
| 10 safety spectacles per inner box | 3660740101084 | 3660740101091 | 3660740101107 | 3660740101114 | 3660740101121 | 3660740101138 | 3660740101145 |
| 200 safety spectacles per outer pack | 3660740201081 | 3660740201098 | 3660740201104 | 3660740201111 | 3660740201128 | 3660740201135 | 3660740201142 |

**CHARACTERISTICS**

| | |
|---|---|
| LENSES | PC - 2,3 mm - Curve 11 |
| FRAME | PC |
| TEMPLES | PC |
| STRAP | Non applicable |
| FOAM | Non applicable |
| SPARE LENSES | No |

10/01/2019

Europe Bollé Safety
34 rue de la soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

**bolle-safety.com**